

TouchView[®] Interactive **ULTRA SERIES, Gen 4**

Collaboration and Interactivity Powered by Simplicity

At TouchView Interactive, we know that schools and businesses want to enhance collaboration and performance without getting bogged down by technology. With a focus on ease-of-use this goal is at the heart of the design of our ULTRA Series, Gen 4.

With 4K resolution, up to 40 points of touch, and an inviting start up screen to engage even the most tentative user, the ULTRA Series features intuitive and powerful whiteboarding tools, reliable bi-directional screen sharing, and easy to access applications folder.

With access to both the Android and Windows environment, the ULTRA series features an NFC reader to log into cloud accounts, and built-in camera and microphone. Perfect tools for video conferencing, distance learning, and flipped classrooms.

Available in sizes from 65" to 98" all ULTRA series panels can be managed by our Remote Device Management solution. Featuring GDPR compliance and Enterprise level security against ransomware and malware, the ULTRA series features IT quick tools to lock system settings. These features ensure our panels are not only ease to use, but easy to confidently manage.

Experience improved collaboration and an enhanced learning environment with a streamlined user experience. **Contact us today to learn more, book a free demo, or to watch a demo now at www.touchview.com/demo.html.**



Ultra High Definition
4K resolution



Responds to
40 simultaneous
points of touch



Embedded WiFi;
Windows, MAC,
and Chrome
compatible

INTERACTIVE SOLUTIONS FOR:



EDUCATION



HOSPITALITY



FINANCE



MANUFACTURING



GOVERNMENT



1-833-TOUCHVW (868-2489)

TouchView Interactive, PO Box 610, Brockton, MA 02301



SPECIFICATIONS

TVULTRA-G4

LCD	Size: 65" / 75" / 86" / 98"*			
Screen Type	D-LED			
Resolution	4K, 3840 x 2160 @ 60Hz			
Display Colors	1.07B (10bit)			
Brightness	65" 350cd/m ²	75" 400cd/m ²	86" 400cd/m ²	98" 450cd/m ²
Contrast Ratio	1200:1 (typ.)			
Response Time	8ms (typ.)			
Viewing Angle	178° (H) / 178° (V)			
Life Time	Full Brightness 30,000 hrs (min.) / ECO 50,000 hrs			
Housing Color	Black Aluminum / Black Metal plate			

* Custom order size

ELECTRICAL

CPU	Chipset	A311D2		
	Architecture	ARM Cortex A73		
	Working Frequency	2.2 GHz		
GPU	Core	Quad Core		
		MaliG52 MP8		
RAM	8GB DDR4			
ROM	64GB			
OS	Android 11.0			
Power Requirements	AC 100 V ~ 240 V, 50/60 Hz			
Power Consumption	65" 300W	75" 380W	86" 460W	98" 480W
	Standby Condition <0.5W			
Audio Output Power	2x15W/8Ω			
OPS Power	DC 18V/5A			

CONNECTIVITY

OPS (optional)	x1	Interface
HDMI IN	x3	Version: HDMI2.0 Up to 3840 x 2160@60Hz
		HDMI2 support ARC function
VGA IN	x1	Interface: DB15 Up to 1920 x 1080@60HZ
USB-C IN	x2	Display/Touch 3840 x 2160@60Hz /209 3A
LAN IN/OUT	x2	10M/100M/1000M Base-T Interface: RJ45
Android USB	x3	1x USB 2.0 2x USB 3.0
Public USB	x2	Version: USB 3.0
Touch-USB	x4	Version: USB 3.0
PC-Audio IN	x1	Input level: 0.2-2Vrms Interface: Φ3.5mm mini interface
RS232 IN	x1	Interface: DB9
HDMI OUT	x1	All signal can be loop-outed
S/PDIF OUT	x1	Type: Optical TOSLINK terminal(Black)
Audio OUT	x1	Output level: 150±20mVrms (@500mVrms,1KHZ) Interface: Φ3.5mm mini interface

WiFi	2.4GHZ / 5GHZ 802.11 A/B/G/N/AC
Bluetooth	2.1 + EDR / 4.2 / 5.0
NFC	ISO/IEC 1443A/B
Camera	4160 x 3120
Microphone	Array - 6 Mic Distance - 24ft.

INTERACTIVITY

Sensing Type	Infrared Touch Frame
Surface Protection	3.2mm Toughened Glass
Infrared Touch	40 Points
Touch Resolution	32768 x 32768
Touch Accuracy	1mm
Writer Tech	High Precision Tool
Touch Tool	Finger Pen Palm
Response Time	≤ 8ms
Theory Clicks	Unlimited
Minimum Touch Object	Single touch ≥ 1.6mm
	Multiple touch ≥ 2mm
Connect Type	USB2.0 Full Speed
Voltage	DC +5V ±5%
Power Consumption	≤ 2W
Windows 11/10/8/7, Android	Multiple Touch
Windows XP, Linux, Mac OS X, Chrome	Single Touch
Palm Detection	Yes
Pens (Included)	Identities - 2

STRUCTURE

	Size	Gross/Net Wt (lbs.)	Width (in.)	Depth (in.)	Height (in.)
Package Size	65"	116/92.8	65.35	9.65	41.14
	75"	160/127	74.02	11.02	45.67
	86"	218/169.6	84.25	11.02	52.76
	98"	348/289	99"	17"	68.5"
Product Dimensions	65"		59.98	3.45	36.23
	75"		67.81	3.43	40.73
	86"		77.48	3.43	46.17
	98"		87.6	3.43	50.4
Fixed Mobile Cart	105/100		68	28	4
Mounting Screw	Type M8				

	Product Size	Height in mm	Width in mm
VESA	65"	600	400
	75"	800	400
	86"	800	600
	98"	800	600